

平键

— 中心沉孔型/中心螺纹沉孔型 —

Order 订货示例

型式 (1Type · 2B) — (3L)

RD-KMPDZ8 — 30

Type	材质	抗拉强度
RD-KMPDZ RD-KMPSZ RD-KMPGZ	S45C	600N/mm ² 以上

型式		(3L) 指定单位5mm	H容差	d	d ₁	h	C	L	公差	
(1Type)	(2B _{h9})									
RD-KMPDZ RD-KMPSZ RD-KMPGZ	8	0	15~80	7	3.4	6	3.5	0.25~0.40	~15	0 -0.18
	10	-0.036	15~80	8	4.5	7.5	4.5	0.40~0.60	16~30	0 -0.21
	12	0	20~80	9	5.5	9.5	5.5		31~50	0 -0.25
	14		30~90	10					51~80	0 -0.30
	16		40~100	11					81~110	0 -0.35
	18		40~110	11						

Type	材质	抗拉强度
RD-KMPDY RD-KMPSY RD-KMPGY	S45C	600N/mm ² 以上

①1个孔既可用于安装, 又可用于螺纹拆卸。

型式		(3L) 指定单位5mm	H容差	拆卸螺纹M (d)	安装用螺栓	d ₁	h	C	L	公差	
(1Type)	(2B _{h9})										
RD-KMPDY RD-KMPSY RD-KMPGY	8	0	15~80	7	M4 (3.5)	M3	6	3.5	0.25~0.40	~15	0 -0.18
	10	-0.036	15~80	8	M5 (4.3)	M4	7.5	4.5	0.40~0.60	16~30	0 -0.21
	12	0	20~80	9						31~50	0 -0.25
	14		30~90	10						51~80	0 -0.30
	16		40~100	11						81~110	0 -0.35
	18		40~110	11							



报价确定

平键

— 螺纹沉孔型/螺纹拆卸型 —

Order 订货示例

型式 (1Type · 2B) — (3L) — (4MPC)

RD-KMPDW8 — 35
RD-KMPDM5 — 30 — MPC8

Type	材质	抗拉强度
RD-KMPDW RD-KMPSW RD-KMPGW	S45C	600N/mm ² 以上

沉孔间距=L-(b×2)

型式		(3L) 指定单位5mm	H容差	d	d ₁	h	b	M (粗牙螺纹)	C	L	公差	
(1Type)	(2B _{h9})											
RD-KMPDW RD-KMPSW RD-KMPGW	8	0	35~80	7	3.4	6	3.5	8	M3	0.25~0.40	~50	0 -0.25
	10	-0.036	45~80	8	4.5	7.5	4.5	10	M4	0.40~0.60	51~80	0 -0.30
	12	0	50~80	9	5.5	9.5	5.5	12	M5		81~110	0 -0.35
	14		50~90	10				14				
	16		50~90	11				15				
	18		60~100	11				16				

Type	材质	抗拉强度
RD-KMPDM RD-KMPSM RD-KMPGM	S45C	600N/mm ² 以上

型式		(3L) 指定单位5mm	H容差	M (粗牙螺纹)	C	L	公差				
(1Type)	(2B _{h9})										
RD-KMPDM RD-KMPSM RD-KMPGM	5	0	10~50	5	0.25~0.40	~10	0 -0.18				
	6	-0.030	10~60	6		M3	11~15	0 -0.18			
	7	0	15~60	7			M4	16~30	0 -0.21		
	8		15~80	8				M5	31~50	0 -0.25	
	10		15~80	9					M6	51~80	0 -0.30
	12		20~80	10						M6	81~110
14	30~90	11									
15	30~90										
16	40~100										
18	40~110										



指定加工

Alterations	Code	Spec.
变更螺纹孔位置	MPC	变更螺纹孔位置。 MPC=指定单位1mm 螺纹拆卸型 M ≤ MPC ≤ L - M



报价确定